



## 615-Duct Tape

### Applications

615 Duct Tape is ideal for retail and non-critical applications.

- Packaging
- Wrapping and Sealing
- Binding and Bundling
- Exterminators
- General Maintenance

### Product Benefits

- High quality utility product
- Consistent tensile
- Even tear in both cross and machine direction
- Excellent conformability to irregular surfaces
- Tested in accordance with UL-723

### Technical Properties

|   |                        |
|---|------------------------|
| Total Thickness   | 8.0mil (0.203mm)       |
| Adhesive Type   | Natural Rubber         |
| Carrier Type  | Dacron® Cloth/P.E Film |
| Color   | Silver                 |
| <i>Values shown are typical. Certified test reports for writing specifications are available.</i> |                        |

## Adhesive Test Data

Adhesion to Steel: 54oz/in.  
Quick Stick to Steel: 16.5oz/in  
Tensile Strength: 18lbs/in.  
Elongation: 18%

The information given and the recommendations made herein are based on our research and are believed to be accurate but no guarantee of their accuracy is made. In every case we urge and recommend that purchasers, before using any product in full scale production, make their own tests to determine to their own satisfaction whether the product is of acceptable quality and is suitable for their particular purposes under their own operating conditions. The products discussed herein are sold without any warranty as to merchantability of fitness for a particular purpose or any other warranty, expressed or implied. No representative of ours has any authority to waive or change the forgoing provisions but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to their needs and to the circumstances prevailing in their business. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

NOTE: Innotec of WI, Inc. does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product (s) or of any final product into which the product (s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform particular purpose desired in any given situation.

**1220 Mound Avenue -Suite 140 – Racine, WI 53404 – (800) 776-7194 – (262) 637-7103 – Fax (262) 637-8205**