



JH757YE-Vinyl Tape

Applications

JH757YE is a 7mil PVC film with a rubber adhesive. The JH757 offers resistance to most chemicals used in electroplating and printed circuit board applications. This conformable and abrasion resistant plastic film is vulnerable to ketones, chlorinated hydrocarbons and esters. Excellent U.V. resistance. Applications include electroplating, harness & pipe wrapping, and printed circuit board masking

- Electroplate masking
- Printed circuit board masking
- Splash protection
- Anodizing

Product Benefits

- Highly conformable
- Controlled unwind
- Clean removal
- Easy to apply. Will not leave residue
- Prevents leakage even on irregular surfaces
- Resists most chemicals in electroplating and circuit board applications
- Vulnerable to ketones

Technical Properties

Total Thickness	7.0mil
Substrate Thickness	6.0mil
Adhesive Type	Rubber
Carrier Type	Polyvinyl chloride
Color	Yellow

Values shown are typical. Certified test reports for writing specifications are available.

Adhesive Test Data

Adhesion to Steel: 20oz/in
Tensile Strength: 18lb/in.
Elongation: 200%
Application Temperature Range: 40°F to 120°F
Operating Temperature Range: -20°F to 170°F

Recommendation

Storage Conditions: 40-60% Humidity, 60°F to 80°F

The information given and the recommendations made herein are based on our research and are believed to be accurate but no guarantee of their accuracy is made. In every case we urge and recommend that purchasers, before using any product in full scale production, make their own tests to determine to their own satisfaction whether the product is of acceptable quality and is suitable for their particular purposes under their own operating conditions. The products discussed herein are sold without any warranty as to merchantability of fitness for a particular purpose or any other warranty, expressed or implied. No representative of ours has any authority to waive or change the forgoing provisions but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to their needs and to the circumstances prevailing in their business. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

NOTE: Innotec of WI, Inc. does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product (s) or of any final product into which the product (s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform particular purpose desired in any given situation.

1220 Mound Avenue -Suite 140 – Racine, WI 53404 – (800) 776-7194 – (262) 637-7103 – Fax (262) 637-8205