



7150-Colored Polypropylene Tape

Applications

7150, tape exhibits excellent adhesion and quick stick. Offers good conformability and high shear strength. Primarily used in web splicing and splice identification applications. Exhibits outstanding bond strength to difficult surfaces: Untreated films, textiles, fabrics, coated papers and other low energy surfaces.

- Splicing films, textiles, fabrics, coated papers and other low energy surfaces
- Web splicing
- Splice identification

Product Benefits

- Good conformability
- High shear strength
- Quick-stick adhesion

Technical Properties

Total Thickness	2.0mil (0.051mm)
Adhesive Type	Water Based Acrylic
Color	8 SHINY COLORS: White, Black, Yellow, Orange, Red, Blue, Green, Purple
<i>Values shown are typical. Certified test reports for writing specifications are available.</i>	

Adhesive Test Data

Adhesion: 22oz/in.

Tensile Strength: 18lbs/in.
Elongation: <180%
Temperature Resistance: 23°F-104°F

The information given and the recommendations made herein are based on our research and are believed to be accurate but no guarantee of their accuracy is made. In every case we urge and recommend that purchasers, before using any product in full scale production, make their own tests to determine to their own satisfaction whether the product is of acceptable quality and is suitable for their particular purposes under their own operating conditions. The products discussed herein are sold without any warranty as to merchantability of fitness for a particular purpose or any other warranty, expressed or implied. No representative of ours has any authority to waive or change the forgoing provisions but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to their needs and to the circumstances prevailing in their business. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

NOTE: Innotec of WI, Inc. does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product (s) or of any final product into which the product (s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform particular purpose desired in any given situation.

1220 Mound Avenue -Suite 140 – Racine, WI 53404 – (800) 776-7194 – (262) 637-7103 – Fax (262) 637-8205