



EPDM CAPS

- Recommended for Painting, Plating, Anodizing and Blasting
- Used to Cap Off Threaded Studs and Tube Ends
- Used to Plug Threaded & Non-Threaded Holes
- Ideal for Curing Temperatures up to 475°F
- Excellent Chemical Resistance & Reusable

ITEM#	INNER DIAM. INCHES	OUTER DIAM. INCHES	LENGTH INCHES	BOX QUANTITY	10 BOXES PRICE PER BOX	TEMP. MAX.
EC600-070	0.070"	0.170"	1.00"	1000	POR	
EC600-080	0.080"	0.200"	0.75"	1000	POR	
EC600-093	0.093"	0.213"	0.50"	1000	POR	
EC600-093A	0.093"	0.195"	0.75"	1000	POR	
EC600-100	0.100"	0.220"	0.50"	1000	POR	
EC600-100A	0.100"	0.200"	1.00"	1000	POR	
EC600-109	0.109"	0.229"	0.50"	1000	POR	
EC600-109A	0.109"	0.215"	0.75"	1000	POR	
EC600-125	0.125"	0.250"	0.50"	1000	POR	
EC600-125A	0.125"	0.250"	1.00"	1000	POR	
EC600-140	0.140"	0.265"	0.50"	1000	POR	
EC600-140A	0.140"	0.265"	1.00"	1000	POR	
EC600-148	0.148"	0.268"	0.50"	1000	POR	
EC600-148A	0.148"	0.268"	0.75"	1000	POR	
EC600-148B	0.148"	0.240"	1.00"	1000	POR	
EC600-156	0.156"	0.280"	0.50"	1000	POR	
EC600-156A	0.156"	0.280"	1.00"	1000	POR	
EC600-172	0.172"	0.276"	0.50"	1000	POR	
EC600-172A	0.172"	0.300"	1.00"	1000	POR	
EC600-172B	0.172"	0.292"	1.50"	1000	POR	
EC600-180	0.180"	0.270"	1.00"	1000	POR	
EC600-187	0.187"	0.315"	0.50"	1000	POR	
EC600-187A	0.187"	0.315"	1.00"	1000	POR	
EC600-197	0.197"	0.317"	0.50"	500	POR	
EC600-218	0.218"	0.338"	1.00"	500	POR	



ITEM#	INNER DIAM. INCHES	OUTER DIAM. INCHES	LENGTH INCHES	BOX QUANTITY	20 BOXES PRICE PER BOX	TEMP. MAX.
EC600-223	0.223"	0.345"	1.50"	500	POR	
EC600-234A	0.234"	0.360"	1.00"	500	POR	
EC600-234B	0.234"	0.354"	1.50"	500	POR	
EC600-250	0.250"	0.370"	1.00"	500	POR	
EC600-260	0.260"	0.380"	1.00"	500	POR	
EC600-281	0.281"	0.400"	1.00"	500	POR	
EC600-295	0.295"	0.415"	0.50"	500	POR	
EC600-295A	0.295"	0.445"	1.00"	500	POR	
EC600-312	0.312"	0.440"	1.00"	500	POR	
EC600-312A	0.312"	0.432"	1.50"	500	POR	
EC600-340	0.340"	0.460"	1.00"	500	POR	
EC600-355	0.355"	0.475"	1.50"	500	POR	
EC600-375	0.375"	0.495"	0.75"	500	POR	
EC600-375A	0.375"	0.495"	1.00"	500	POR	
EC600-375B	0.375"	0.495"	1.50"	500	POR	
EC600-406	0.406"	0.531"	1.00"	500	POR	
EC600-437	0.437"	0.565"	1.00"	500	POR	
EC600-456	0.456"	0.556"	1.50"	500	POR	
EC600-468	0.468"	0.593"	1.00"	500	POR	
EC600-480	0.480"	0.605"	1.50"	500	POR	
EC600-500	0.500"	0.605"	1.50"	500	POR	
EC600-535	0.535"	0.635"	1.50"	250	POR	
EC600-535A	0.535"	0.655"	3.00"	250	POR	
EC600-562	0.562"	0.682"	1.50"	250	POR	
EC600-600	0.600"	0.708"	1.50"	250	POR	
EC600-625	0.625"	0.708"	1.50"	250	POR	
EC600-625A	0.625"	0.750"	2.50"	250	POR	
EC600-687	0.687"	0.812"	1.50"	250	POR	
EC600-730	0.730"	0.855"	1.50"	250	POR	
EC600-750	0.750"	0.875"	1.50"	250	POR	
EC600-780	0.780"	0.905"	1.50"	250	POR	
EC600-812	0.812"	0.937"	1.50"	250	POR	
EC600-875	0.875"	1.000"	1.50"	250	POR	
EC600-937	0.937"	1.062"	1.50"	250	POR	
EC600-970	0.970"	1.095"	1.50"	250	POR	
EC600-1000	1.000"	1.125"	1.50"	250	POR	
EC600-1000A	1.000"	1.120"	2.00"	250	POR	
EC600-1062	1.062"	1.187"	2.00"	100	POR	
EC600-1125	1.125"	1.250"	1.50"	100	POR	
EC600-1187	1.187"	1.312"	1.50"	100	POR	
EC600-1250	1.250"	1.375"	1.50"	100	POR	

