



- Recommended for Painting, Plating, Anodizing and Blasting
- Used to Plug Threaded and Non-Threaded Through Holes.
- Ideal for Curing Temperatures up to 475°F
- Excellent Sealing Capability, High Chemical Resistance & Reusable

EPDM PULL PLUGS

ITEM#	MAJOR DIAM. A INCHES	MINOR DIAM. B INCHES	MAJOR LENGTH C INCHES	MINOR LENGTH D INCHES	BOX QUANTITY	10 BOXES PRICE PER BOX	TEMP. MAX.
EPP600-0067	0.067"	0.047"	0.625"	0.625"	500	POR	
EPP600-0073	0.073"	0.047"	0.625"	0.625"	500	POR	
EPP600-0093	0.093"	0.062"	0.625"	0.625"	500	POR	
EPP600-0105	0.105"	0.070"	1.000"	1.000"	500	POR	
EPP600-0109	0.109"	0.062"	0.625"	0.625"	500	POR	
EPP600-0118	0.118"	0.082"	1.000"	1.000"	500	POR	
EPP600-0125	0.125"	0.082"	0.625"	0.625"	500	POR	
EPP600-0130	0.130"	0.082"	0.625"	0.625"	500	POR	
EPP600-0140	0.140"	0.062"	0.625"	0.625"	500	POR	
EPP600-0141	0.141"	0.086"	0.625"	0.625"	500	POR	
EPP600-0156	0.156"	0.082"	0.625"	0.625"	500	POR	
EPP600-0158A	0.158"	0.093"	1.000"	1.000"	500	POR	
EPP600-0158B	0.158"	0.093"	1.000"	1.500"	500	POR	
EPP600-0162	0.162"	0.093"	0.625"	0.625"	500	POR	
EPP600-0180	0.180"	0.110"	0.625"	0.625"	500	POR	
EPP600-0187	0.187"	0.110"	1.000"	1.000"	500	POR	

ITEM#	MAJOR DIAM. A INCHES	MINOR DIAM. B INCHES	MAJOR LENGTH C INCHES	MINOR LENGTH D INCHES	BOX QUANTITY	20 BOXES PRICE PER BOX	TEMP. MAX.
EPP600-0197A	0.197"	0.110"	1.000"	1.000"	500	POR	
EPP600-0197B	0.197"	0.110"	1.000"	1.500"	500	POR	
EPP600-0217	0.217"	0.125"	0.984"	0.984"	500	POR	
EPP600-0218	0.218"	0.125"	1.000"	1.000"	500	POR	
EPP600-0225	0.225"	0.125"	1.000"	1.000"	500	POR	
EPP600-0257	0.257"	0.125"	1.000"	1.000"	500	POR	
EPP600-0275	0.275"	0.130"	0.950"	0.950"	500	POR	
EPP600-0281	0.281"	0.138"	1.000"	1.000"	500	POR	
EPP600-0312	0.312"	0.147"	1.000"	1.000"	500	POR	
EPP600-0335	0.335"	0.157"	1.000"	1.000"	500	POR	
EPP600-0350	0.350"	0.157"	1.000"	1.000"	500	POR	
EPP600-0388	0.388"	0.157"	1.000"	1.000"	250	POR	
EPP600-0400	0.400"	0.157"	1.000"	1.000"	250	POR	
EPP600-0410	0.410"	0.157"	1.000"	1.000"	250	POR	
EPP600-0414	0.414"	0.157"	1.000"	1.000"	250	POR	
EPP600-0445	0.445"	0.157"	1.000"	1.000"	250	POR	
EPP600-0468	0.468"	0.250"	1.000"	1.000"	250	POR	
EPP600-0510	0.510"	0.250"	1.000"	1.000"	100	POR	
EPP600-0530	0.530"	0.250"	1.000"	1.000"	100	POR	
EPP600-0612	0.612"	0.250"	1.000"	1.000"	100	POR	
EPP600-0640	0.640"	0.375"	1.000"	1.000"	100	POR	
EPP600-0700	0.700"	0.375"	1.000"	1.000"	100	POR	
EPP600-0729	0.729"	0.315"	1.000"	1.000"	100	POR	
EPP600-0770	0.770"	0.375"	1.125"	1.125"	50	POR	
EPP600-0809	0.809"	0.315"	1.000"	1.000"	50	POR	
EPP600-0896	0.896"	0.375"	1.000"	1.000"	50	POR	
EPP600-1020	1.020"	0.375"	1.000"	1.000"	50	POR	