

# INNOTEC of WISCONSIN, Inc.

## SILICONE RUBBER

### SOLID RUBBER

#### FEATURES:

- ✦ Grades: 30-70 Durometer, Fabric Reinforced, Flame Retardant & Thermally Conductive
- ✦ Thickness: 1/32"-1/8"
- ✦ Adhesive: Silicone or Acrylic
- ✦ Stock Sizes: 36" x 36" Sheets

#### APPLICATIONS:

- ✦ Shrink Tunnel Curtains
- ✦ Channel Cushion on heat sealing equipment
- ✦ Insulation & Vibration Dampening
- ✦ Gasketing & Sealing
- ✦ Sound & Shock Absorption
- ✦ Fire Blocking & Electrical Insulation
- ✦ Spacing & Surface Protection
- ✦ Padding & Thermal Barrier



Available with Adhesive

### SPONGE RUBBER

#### FEATURES:

- ✦ Grade: Soft, Medium-Soft, Medium-Firm, Firm, Fabric Reinforced, Flam Retardant, Fluorosilicone & Thermally Conductive
- ✦ Thickness: 1/32"-3/4"
- ✦ Adhesive: Silicone or Acrylic
- ✦ Stock Sizes: 36" x 36" sheets

#### APPLICATIONS:

- ✦ Channel cushion on heat sealing equipment
- ✦ Press Pads & Insulation
- ✦ Vibration Dampening
- ✦ Gasketing & Sealing
- ✦ Sound & Shock Absorption
- ✦ Fire Blocking & Electrical Insulation
- ✦ Spacing & Surface Protection
- ✦ Padding & Thermal Barrier

### CUSTOM MOLDING CAPABILITIES

- ✦ Die Cutting
- ✦ Water Jet Cutting
- ✦ Extruding

800-776-7194