



SILICONE PLUGS

- Recommended for Powder Coating, E-Coating, Plating & Anodizing
- Used to Plug Threaded and Non-Threaded Holes
- Ideal for Curing Temperatures up to 600°F
- Excellent Sealing Capability, Highly Reusable & Color Coded Product available for Easy Identification

ITEM#	BOTTOM DIAM. INCHES	TOP DIAM. INCHES	LENGTH INCHES	BOX QUANTITY	10 BOXES PRICE PER BOX	TEMP. MAX.
-------	---------------------	------------------	---------------	--------------	------------------------	------------

P600-031	0.031"	0.125"	0.625"	1000	POR
P600-062	0.062"	0.125"	0.625"	1000	POR
P600-062A	0.062"	0.187"	0.625"	1000	POR
P600-062B	0.062"	0.187"	0.750"	1000	POR
P600-125	0.125"	0.250"	0.750"	1000	POR
P600-125A	0.125"	0.250"	1.000"	1000	POR
P600-187	0.187"	0.344"	0.625"	1000	POR
P600-187A	0.187"	0.344"	1.000"	1000	POR

ITEM#	BOTTOM DIAM. INCHES	TOP DIAM. INCHES	LENGTH INCHES	BOX QUANTITY	20 BOXES PRICE PER BOX
-------	---------------------	------------------	---------------	--------------	------------------------

P600-125B	0.125"	0.375"	1.000"	100	POR
P600-125C	0.125"	0.500"	2.000"	100	POR
P600-250	0.250"	0.375"	0.750"	100	POR
P600-250A	0.250"	0.437"	1.000"	100	POR
P600-312	0.312"	0.500"	1.000"	100	POR
P600-344	0.344"	0.438"	0.687"	100	POR
P600-375	0.375"	0.563"	1.000"	100	POR
P600-406	0.406"	0.594"	1.000"	100	POR



ITEM#	BOTTOM DIAM. INCHES	TOP DIAM. INCHES	LENGTH INCHES	BOX QUANTITY	20 BOXES PRICE PER BOX	TEMP. MAX.
P600-438	0.438"	0.625"	0.813"	100	POR	
P600-500	0.500"	0.656"	1.000"	100	POR	
P600-563	0.563"	0.750"	1.000"	100	POR	
P600-625	0.625"	0.812"	0.812"	100	POR	
P600-719	0.719"	0.938"	1.000"	100	POR	
P600-787	0.787"	1.024"	1.000"	100	POR	
P600-905	0.905"	1.063"	1.000"	100	POR	
P600-938	0.938"	1.102"	1.000"	100	POR	
P600-1024	1.024"	1.260"	1.000"	100	POR	
P600-1063	1.063"	1.338"	1.000"	100	POR	
P600-1188	1.188"	1.456"	1.000"	1	POR	
P600-1250	1.250"	1.531"	1.000"	1	POR	
P600-1313	1.313"	1.614"	1.000"	1	POR	
P600-1417	1.417"	1.693"	1.000"	1	POR	
P600-1469	1.469"	1.772"	1.000"	1	POR	
P600-1500	1.500"	1.810"	1.000"	1	POR	
P600-1625	1.625"	1.968"	1.000"	1	POR	
P600-1750	1.750"	2.086"	1.000"	1	POR	
P600-1875	1.875"	2.205"	1.000"	1	POR	
P600-1969	1.969"	2.480"	1.000"	1	POR	
P600-2125	2.125"	2.520"	1.000"	1	POR	
P600-2281	2.281"	2.677"	1.000"	1	POR	
P600-2438	2.438"	2.953"	1.375"	1	POR	
P600-3000	3.000"	3.500"	1.500"	1	POR	
P600-3250	3.250"	4.055"	1.500"	1	POR	
P600-3500	3.500"	5.000"	2.000"	1	POR	

