

Kapton / Polyimide Tapes

| Item# | Width Decimal | Width Inches | Length Yards | Rolls Per Case | Temp Max. |
|-------|------------------|-----------------|-----------------|-------------------|--------------|
| JM511 | 0.250" | 1/4" | 36 | 144 | 500° F |
| JM511 | 0.375" | 3/8" | 36 | 96 | 500° F |
| JM511 | 0.500" | 1/2" | 36 | 72 | 500° F |
| JM511 | 0.625" | 5/8" | 36 | 60 | 500° F |
| JM511 | 0.750" | 3/4" | 36 | 48 | 500° F |
| JM511 | 0.875" | 7/8" | 36 | 40 | 500° F |
| JM511 | 1.000" | 1" | 36 | 36 | 500° F |
| JM511 | 1.125" | 1 1/8" | 36 | 32 | 500° F |
| JM511 | 1.250" | 1 1/4" | 36 | 30 | 500° F |
| JM511 | 1.375" | 1 3/8" | 36 | 24 | 500° F |
| JM511 | 1.500" | 1 1/2" | 36 | 24 | 500° F |
| JM511 | 1.750" | 1 3/4" | 36 | 24 | 500° F |
| JM511 | 2.000" | 2" | 36 | 24 | 500° F |
| JM511 | 2.500" | 2 1/2" | 36 | 24 | 500° F |
| JM511 | 3.000" | 3" | 36 | 16 | 500° F |
| JM511 | 3.500" | 3 1/2" | 36 | 16 | 500° F |
| JM511 | 4.000" | 4" | 36 | 12 | 500° F |
| JM511 | 4.500" | 4 1/2" | 36 | 12 | 500° F |
| JM511 | 5.000" | 5" | 36 | 10 | 500° F |
| JM511 | 5.500" | 5 1/2" | 36 | 10 | 500° F |
| JM511 | 6.000" | 6" | 36 | 8 | 500° F |
| JM511 | 12.000" | 12" | 36 | 4 | 500° F |
| JM511 | 18.000" | 18" | 36 | 1 | 500° F |

Kapton Discs

| Item# | Diameter Decimal | Diameter Inches | Pieces Per Roll | Temp Max. |
|-------|---------------------|--------------------|--------------------|--------------|
| 501DR | 0.125" | 1/8" | 5000 | 500° F |
| 501DR | 0.187" | 3/16" | 5000 | 500° F |
| 501DR | 0.250" | 1/4" | 5000 | 500° F |
| 501DR | 0.312" | 5/16" | 5000 | 500° F |
| 501DR | 0.375" | 3/8" | 5000 | 500° F |
| 501DR | 0.394" | 10mm | 5000 | 500° F |
| 501DR | 0.437" | 7/16" | 5000 | 500° F |
| 501DR | 0.472" | 12mm | 2500 | 500° F |
| 501DR | 0.500" | 1/2" | 2500 | 500° F |
| 501DR | 0.562" | 9/16" | 2500 | 500° F |
| 501DR | 0.590" | 15mm | 2500 | 500° F |
| 501DR | 0.625" | 5/8" | 2000 | 500° F |
| 501DR | 0.750" | 3/4" | 2000 | 500° F |
| 501DR | 0.875" | 7/8" | 2000 | 500° F |
| 501DR | 0.984" | 25mm | 2000 | 500° F |
| 501DR | 1.000" | 1" | 2000 | 500° F |
| 501DR | 1.250" | 1 1/4" | 1000 | 500° F |
| 501DR | 1.750" | 1 3/4" | 1000 | 500° F |
| 501DR | 1.960" | 50mm | 500 | 500° F |
| 501DR | 2.000" | 2" | 500 | 500° F |
| 501DR | 3.500" | 3 1/2" | 500 | 500° F |
| 501DR | 4.000" | 4" | 250 | 500° F |
| 501DR | 5.000" | 5" | 250 | 500° F |